

GHIBLI

FINISHES



PRODUCT DESCRIPTION

Description Decorative paint for interiors with a textured effect, with a matt finish.

Intended use Indoors
On new smooth surfaces or on adequately treated old paintwork.

Main features Matt sandblasted decorative effect.
High coverage.
Single coat.

Main technical data

Technical information	Method	Main data at 20°C and 60% of R.H.
Theoretical yield per coat	ISO 7254	8÷10 m ² /L

Available colours White and other colours achievable with the tintometric system. For colour selection, refer to the Color Collection Ghibli chart.

LAYING

Dilution and preparation of the product The product is ready to use.

Application tools

Soft bristle brush (spalter type).
Stir thoroughly before application.

Preparation of the substrate

NEW WALL SURFACES

Concrete, plasterboard and cement-based plasters: make sure that the substrate is perfectly seasoned; always apply at least one coat of MULTIQUARTZ base coat to regulate absorption and wait for it to dry completely.

OLD SURFACES ALREADY PAINTED OR PARTIALLY DEGRADED

In case of dirt and mould, before carrying out any operation, it is necessary to perform a treatment with specific anti-mould sanitising products, taking care to leave them to act before carrying out a suitable cleaning.

Carry out a careful scraping (mechanical or manual) in order to remove every element that is detaching or in any case is not perfectly cohesive and anchored to the substrate; assess if the complete removal of old paint is necessary.

In case of dusting and chalking, it is necessary to apply a coat of PRYMER ACQ water-based acrylic fixative; after 6-8 hours, apply a coat of MULTIQUARTZ base coat and wait for it to dry completely (6-8 hours) before applying the decorative finish.

WALL SURFACES WITH LIME PLASTER OR CEMENT-LIME MORTAR

In case of dusting and chalking, it is necessary to apply a coat of SILICA FONDO SD; after 24 hours, apply a coat of MULTIQUARTZ and wait for it to dry completely (6-8 hours) before applying the decorative finish.

In the case of cohesive and compact substrate, it will be sufficient to apply a coat of MULTIQUARTZ and wait for it to dry completely (6-8 hours) before applying the decorative finish.

WARNING: in the presence of a mineral substrate it is technically correct to assess whether to prefer applying a mineral or lime-based decorative finish, in order not to alter the breathability of the substrates.

Application system

Apply one coat of GHIBLI using random or overlapping brush strokes.

- Touch dry: Max 1 h
- Dry in depth: Max 24 h
- Overcoat: after 4÷5 h

Conditions of application

Conditions of the environment and support:

- Environment temperature min. +5°C / max. +35°C;
- Relative humidity of the environment <75%
- Substrate temperature min. +5°C / max. +35°C
- Substrate humidity <10% of R.H.

Practical advice

- Do not apply on surfaces exposed to direct sunlight or in the presence of strong drafts
- Store the product in its original container at a temperature between +5°C and +35°C

Known incompatibilities

None.
For any use other than that indicated in this technical data sheet, contact our Technical Assistance Service.

Cleaning of tools

With water immediately after use.

Safety Precautions

- Keep the container tightly closed after use, away from heat sources, away from frost and direct sunlight
- The safety information for the user is contained in the relevant safety data sheet
- Empty containers must be disposed of in compliance with local regulations.

OTHER INFORMATION

Classification (UNI 8681)

B4. C.O.A.2.HC
Aqueous dispersion, single-component, hard drying, matt, vinyl top coat paint.

VOC classification (Directive 2004/42/EC)

Matt paints for indoor walls and ceilings.
EU VOC limit value for GHIBLI (cat. A/a): 30 g/L (2010). GHIBLI contains a maximum of 30 g/L of VOC.

Other technical information

Technical information	Method	Main data at 20°C and 60% of R.H.
Appearance and finish		Matt
Density	ISO 2811-1	approx. 1.558 g/ml
Brookfield viscosity	ASTM D 2196	approx. 4500 cps
Flash point	UNI 8909	Non-flammable
Storage life	UNI 10154	At least 12 months
Binder		Vinyl

ITEM SPECIFICATIONS

Application of GHIBLI decorative effect paint.

GHIBLI is applied using a roller or brush, with an approximate yield per coat of 8÷10 m²/L, depending on substrate absorption.

Price on site € _____ per m² including materials, labour and excluding scaffolding, protections and any surface preparation.

All the technical indications contained herein are the result of our best experience, are indicative and do not constitute a guarantee of results. The data and methods shown on this technical data sheet can be modified at any time depending on any change in production technologies. The application of the products takes place outside our control and therefore falls under the sole responsibility of the customer. The correct use of the materials assumes compliance with the general requirements for use set out in the GENERAL CONSIDERATIONS page of the PRODUCT INFORMATION SHEETS collection and in particular with what is indicated in this sheet, especially with regard to the preparation and suitability of the supports. The technical service of Cromology Italia spa is available to users to provide additional information to that reported here. THIS DATA SHEET REPEALS AND REPLACES ANY PREVIOUS EDITION.

CROMOLOGY ITALIA SpA ORGANISATION WITH QUALITY, SAFETY AND ENVIRONMENTAL MANAGEMENT SYSTEM ISO 9001, OHSAS 18001, ISO 14001 CERTIFIED BY BUREAU VERITAS SpA.

PROFESSIONAL USE ONLY